

Nokia 7368 ISAM ONT G-240W-G

Residential gateway ONT

The Nokia 7368 Intelligent Services Access Manager (ISAM) optical network terminal (ONT) G-240W-G is the solution for home networking that is delivered by Gigabit Passive Optical Network (GPON). The device has built-in concurrent dual-band Wi-Fi® 802.11 b/g/n and 802.11ac networking with triple play capabilities that simplify the home equipment experience. It can provide these triple play services that include voice, video and data using high-capacity Wi-Fi connectivity.

The Nokia 7368 ISAM ONT G-240W-G is designed to take advantage of Nokia award-winning management platforms. These platforms include a customized Motive™ Home Device Manager, which is integrated with the Nokia 5520 Access Management System (AMS) platform to deliver a uniform end-to-end operations, administration, and maintenance (OA&M) solution that carriers need to provide subscriber satisfaction.

This Nokia indoor ONT is designed to deliver triple play services (voice, video and data) to residential subscribers. Voice services are provided through two plain old telephone service (POTS) ports with an integrated analog telephone adapter (ATA) that converts voice traffic into Session Initiation Protocol (SIP). Connectivity to an existing public switched telephone network (PSTN) Class 5 switch is supported through SIP with direct interoperability of a variety of soft switches. Ethernet connectivity is available on four Gigabit Ethernet (GigE) ports, all of which have the ability to burst up to a full gigabit



dynamically. Service providers can deliver video using IP packets (IPTV).

Relying on dual-band Wi-Fi allows for support of the widest range of customer products. The IEEE 802.11ac standard enables gigabit speeds on many newer devices, while the widely supported 802.11b/g/n standard can simultaneously connect to legacy devices.

Features

- Four RJ-45 10/100/1000 Ethernet ports
- Two POTS ports for carrier-grade voice services
- Two USB 2.0 host ports
- Dual-band concurrent Wi-Fi: 2.4G and 5G
- Wireless IEEE 802.11 b/g/n: 2.4G
- Wireless IEEE 802.11ac: 5G
- Network Address Translation (NAT) and firewall
- Voice interworking function from the analog POTS lines to the voice over IP (VoIP) and Ethernet layers
- Optics support received signal strength indication (RSSI)
- Supports virtual private network (VPN) pass-through for Point-to-Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP) and IPSec
- Port forwarding and demilitarized zone (DMZ)/dynamic domain name system (DDNS)

Benefits

- Integrates the ONT and wireless access point functions to allow for one less device in the home
- Delivers connectivity to Ethernet devices within the home
- Supports full triple play services, including voice, video and data
- Allows service-per-port configurations
- Supports IP video distribution
- Supports easy-to-use USB 2.0 connections for external disk drives and home network attached storage (NAS)
- Delivers voice services using VoIP
- Delivers video services efficiently with multicasting or unicasting
- Facilitates network management using Nokia 5520 AMS
- Flexible video delivery options of Ethernet or wireless to set-top boxes (STBs)

Technical specifications

Physical

- Height: 170 mm (6.7 in)
- Width: 240 mm (9.4 in)
- Depth: 32 mm (1.3 in)

Installation

- Wall or desk mountable

Operating environment

- Temperature: -5°C to 45°C (23°F to 113°F)
- Relative humidity: 10% to 90%

Power requirements

- Local powering with 12 V input (feed uses external AC/DC adapter)
- Dying gasp support
- Power consumption: <30 W

GPON uplinks

- Wavelength: 1490 nm downstream, 1310 nm upstream
- Line rate: 2.488 Gb/s downstream, 1.244 Gb/s upstream
- GPON Encapsulation Method (GEM) mode support for IP/Ethernet service traffic
- ITU-T G.984.3-compliant dynamic bandwidth reporting
- ITU-T G.984.3-compliant Advanced Encryption Standard (AES) in downstream
- ITU-T G.984.3-compliant forward error correction (FEC)
- ITU-T G.988 Appendix 1 and Appendix 2 ONT Management Control Interface (OMCI)
- Remote software image download
- Small form factor (SFF) type laser, SC/APC connector

Ethernet interfaces

- 10/100/1000Base-T interface with RJ-45 connectors
- Forwarding



- Ethernet port auto-negotiation or manual configuration with medium dependent interface/medium dependent interface crossover (MDI/MDIX)
- Virtual switch based on IEEE 802.1q virtual LAN (VLAN)
- VLAN tagging/detagging per Ethernet port and marking/remarking of IEEE 802.1p
- IP type of service/differentiated services code point (ToS/DSCP) to IEEE 802.1p mapping for untagged frames
- Class of service (CoS) based on VLAN ID, IEEE 802.1p bit
- Internet Group Management Protocol (IGMP) v2/v3 snooping

POTS interfaces

- Two FXS ports for VoIP service with RJ-11 connectors
- Multiple codecs: ITU-T G.711, ITU-T G.729
- SIP (RFC 3261)
- ITU-T G.168 echo cancellation
- Services: caller ID, call waiting, call hold, 3-way call, call transfer, message waiting indication
- 5 ringer equivalence numbers (RENS) per line
- Dual-tone multi-frequency (DTMF) dialing
- Balanced sinusoidal ring signal, 55 V root mean square (RMS)

WLAN interfaces

- 2x2 802.11b/g/n
- 3x3 802.11ac
- 64-bit and 128-bit Wired Equivalent Privacy (WEP) support

- Wi-Fi Protected Access (WPA) support, including pre-shared key (WPA-PSK) and WPA2
- Media access control (MAC) filters

USB interface

- Two USB 2.0 interfaces

Residential gateways

- IPv4 and IPv6
- Point-to-Point Protocol over Ethernet (PPPoE) and IP over Ethernet (IPoE)
- NAT, DMZ and firewall
- Dynamic Host Configuration Protocol (DHCP) and domain name system (DNS) proxy
- IGMP proxy
- Supports TR-069

LEDs

- Power
- Link
- Auth
- LAN (1~4)
- TEL (1~2)
- VoIP
- Wi-Fi Protected Setup (WPS) 2.4G/5G
- WLAN 2.4G/5G
- USB
- Internet

Safety and electromagnetic interference (EMI)

- Protection of over voltage/current

Regulatory compliances

- CE Mark
- FCC Mark

About Nokia

We create the technology to connect the world. Powered by the research and innovation of Nokia Bell Labs, we serve communications service providers, governments, large enterprises and consumers, with the industry's most complete, end-to-end portfolio of products, services and licensing.

From the enabling infrastructure for 5G and the Internet of Things, to emerging applications in digital health, we are shaping the future of technology to transform the human experience. networks.nokia.com

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

© 2018 Nokia

Nokia Oyj
Karaportti 3
FI-02610 Espoo, Finland
Tel. +358 (0) 10 44 88 000

Document code: SR1809028547EN (September) CID 205620